





LUPROMAX AEGLE 5000

NATO Stock No. 6850-32-087-9464

Synthetic Engine Oil 10W-40



DESCRIPTION

LLUPROMAX Oil with Heat Activated Technology™ is specially developed to LUbricate, PROtect and MAXimize your engine performance.

LUPROMAX AEGLE 5000 10W-40 is an advanced synthetic engine oil designed to keep your engine running like new by providing exceptional wear protection and overall performance for a smooth driving experience. The advanced synthetic technology provides maximum acceleration, torque and power for outstanding performance and reliability.

LUPROMAX AEGLE 5000 10W-40 with Heat Activated Technology™ contains LUPROMAX's proven synthetic technology that provides a high level of protection, reduced vibration and engine noise, and enhanced shear stability for a quieter and smoother drive.

LUPROMAX Oil is engineered to provide maximum power for your driving experience.

ADVANTAGES

- Help maintain engine cleanliness and continuously prevent dirt and sludge build-up.
- Tested and proven to deliver improved power and acceleration.
- Excellent wear protection at high temperatures.
- Outstanding resistance to corrosion helps extend life of critical wear surfaces.
- Excellent flow characteristics under extreme hot and cold operating conditions and during periods of intermittent use.
- Excellent anti-oxidation properties to prevent premature ageing
- Reduced friction and engine noise, enhances shear stability for a quieter, smoother and enjoyable drive.

















LUPROMAX AEGLE 5000

NATO Stock No. 6850-32-087-9464

Synthetic Engine Oil 10W-40

APPLICATIONS

LUPROMAX AEGLE 5000 10W-40 is designed to optimize performance and protection for modern passenger cars where API SM (and below) are recommended.

 LUPROMAX AEGLE 5000 10W-40 is specially design to give you confidence of protection beyond that of conventional oils.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

LUPROMAX AEGLE is unlikely to present any significant health or safety hazard when used properly in the recommended application provided in the Material Safety Data Sheet (MSDS) are followed.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained upon request through your sales contract office, or via the internet.

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

TYPICAL PROPERTIES

Properties				Method	LUPROMAX AEGLE 5000 10W-40
SAE Viscosity Grade				SAE J 300	10W-40
Kinematic Viscosity		@40°C	cSt	ASTM D445	95.23
Kinematic Viscosity		@100°C	cSt	ASTM D445	14.54
Viscosity Index				ASTM D2270	159
TBN	mgKOH/	g		ASTM D2896	7.39
Flash Point	OC			ASTM D92	225
Pour Point	оС			ASTM D97	-36
Density	@15°C	kg/l		ASTM D4052	0.862

AVAILABLE PACKAGING

20 liters pail/ 200 liters drum





For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed	by:



Headquarters & Far East Office: Magna International Pte Ltd

10H Enterprise Road Singapore 629834 **Tel** (65) 6788-1228 Fax (65) 6785-1497 Email info@magnachem.com.sg Website http://www.magnachem.com.sg

ISO 9001





ISO 14001

Indonesia Office: PT Magna Indonesia

Central Park Office Tower, 18th floor Suite #2 Jl. Letjen S. Parman Kav. 28 Jakarta Barat 11470 Tel (62)021-2903 4333 Fax (62) 021-2903 4260 Email contactus@lupromax.co.id

North America Office:

1450 Government Rd West Kirkland Lake Ontario P2N 2E9 Canada Email magna@vappro.com

Australia Office:

6/632-542 Hampton Street. Hampton VIC 3188 Melbourne Australia

Email

nelsoncheng@magnaaustralia.com.au Website

http://www.magnaaustralia.com.au

This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.