

**SYNTHETIC ENGINE OIL
FOR SCOOTERS 10W-30
AEGLE SERIES**

NATO Stock No. 6850-32-087-9449

AEGLE MATIC

LUPROMAX





Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX[®]
Lubricates • Protects • Maximizes

LUPROMAX AEGLE MATIC

NATO Stock No. 6850-32-087-9449

Synthetic Engine Oil 10W-30



DESCRIPTION

LUPROMAX Oil with Heat Activated Technology™ is specially developed to LUBricate, PROtect and MAXimize your engine performance.

LUPROMAX AEGLE MATIC 10W-30 is designed specifically for scooter owners who love the exhilaration of riding. This technology enables highest performance in shift-feeling, acceleration, torque and power.

LUPROMAX AEGLE MATIC 10W-30 with Heat Activated Technology™ provides a high level of protection, reduced vibration and engine noise, and enhanced shear stability for a quieter and smoother ride.

LUPROMAX Oil is engineered to perform maximum power for your riding experience.

ADVANTAGES

- Help maintain engine cleanliness and continuously prevent dirt and sludge build-up
- Tested and proven to deliver improved power and acceleration at the touch of the throttle
- Excellent wear protection at high temperatures and highly effective protection from corrosion
- Excellent flow characteristics under extreme hot and cold operating conditions and contributes to fuel economy
- Good anti-oxidation properties to prevent premature ageing of oil
- Advanced control by smoothing clutch engagement, gear changes and preventing slippage
- Reduced friction and engine noise, enhances shear stability for a quieter and smoother ride





Revolutionizing the Lubrication Industry through Heat Activated Technology



LUPROMAX AEGLE MATIC

NATO Stock No. 6850-32-087-9449

Synthetic Engine Oil
10W-30

APPLICATIONS

LUPROMAX AEGLE MATIC 10W-30 is designed to optimize performance and protection for modern scooters where JASO MB is recommended.

- LUPROMAX AEGLE MATIC 10W-30 is specifically recommended for lubrication of modern scooter engines.
- LUPROMAX AEGLE MATIC 10W-30 is specially design to give you confidence of protection beyond that of conventional oils.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

TYPICAL PROPERTIES

Properties		Method	LUPROMAX AEGLE MATIC
SAE Viscosity Grade		SAE J 300	10W-30
Kinematic Viscosity	@40°C	cSt ASTM D445	67.32
Kinematic Viscosity	@100°C	cSt ASTM D445	10.98
Viscosity Index		ASTM D2270	155
TBN	mgKOH/g	ASTM D2896	6.73
Flash Point	°C	ASTM D92	218
Pour Point	°C	ASTM D97	-33
Density	@15°C	kg/l ASTM D4052	0.859

AVAILABLE PACKAGING

20 liters pail/ 200 liters drum

HEALTH, SAFETY & ENVIRONMENT

• Health and Safety

LUPROMAX AEGLE is unlikely to present any significant health or safety hazard when used properly in the recommended application provided in the Material Safety Data Sheet (MSDS) are followed.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained upon request through your sales contract office, or via the internet.

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.





Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX[®]

For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed by:



Headquarters & Far East Office:
Magna International Pte Ltd

10H Enterprise Road
Singapore 629834

Tel (65) 6788-1228

Fax (65) 6785-1497

Email info@magnachem.com.sg

Website

<http://www.magnachem.com.sg>

Indonesia Office:

PT Magna Indonesia

Central Park Office Tower,
18th floor Suite #2

Jl. Letjen S. Parman Kav. 28
Jakarta Barat 11470

Tel (62)021-2903 4333

Fax (62) 021-2903 4260

Email contactus@lupromax.co.id

North America Office:

1450 Government Rd West
Kirkland Lake Ontario P2N 2E9
Canada

Email magna@vappro.com

Australia Office:

6/632-542 Hampton Street,
Hampton VIC 3188
Melbourne Australia

Email

nelsoncheng@magnaaustralia.com.au

Website

<http://www.magnaaustralia.com.au>

ISO 9001



Certificate No: AJA800-2706

ISO 14001



Certificate No: AJA1316783

This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.