

SYNTHETIC ENGINE OIL 5W-30

ZELOS SERIES

NATO Stock No 6850-32-087-9468

ZELOS 5000



LUPROMAX





Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX®
Lubricates • Protects • Maximizes

LUPROMAX ZELOS 5000

NATO Stock No. 6850-32-087-9468

Synthetic Engine Oil
5W-30

DESCRIPTION

LUPROMAX Oil with Heat Activated Technology™ is specially developed to LUBricate, PROtect and MAXimize your engine performance.

LUPROMAX ZELOS 5000 5W-30 is an advanced synthetic engine oil designed to keep your engine running like new by providing exceptional wear protection and overall performance for a smooth driving experience. The advanced synthetic technology enables maximum acceleration, torque and power for outstanding performance and reliability.

The 5W-30 viscosity grade is one of the most recommended viscosity grades for new cars. LUPROMAX ZELOS 5000 5W-30 with Heat Activated Technology™ contains LUPROMAX's proven synthetic technology that provides a high level of protection, reduced vibration and engine noise, and enhanced shear stability for a quieter and smoother drive.

LUPROMAX Oil is engineered to provide maximum power for your driving experience.

LUPROMAX Oil is engineered to provide maximum power for your driving experience.

LUPROMAX – LUBRICATES, PROTECTS & MAXIMIZES your engine performance.

ADVANTAGES

- Help maintain engine cleanliness and continuously prevent dirt and sludge build-up
- Tested and proven to deliver improved power and acceleration
- Excellent wear protection at high temperatures
- Outstanding resistance to corrosion helps extend life of critical wear surfaces
- Outstanding performance during the maximum oil change interval and contributes greater fuel efficiency
- Excellent flow characteristics under extreme hot and cold operating conditions and during periods of intermittent use
- Excellent anti-oxidation properties to prevent premature ageing of oil
- Reduced friction and engine noise, enhances shear stability for a quieter and smoother drive



NATO STOCK NUMBER
LISTED ON NATO MCRL





Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX[®]
Lubricates • Protects • Maximizes

LUPROMAX ZELOS 5000

NATO Stock No. 6850-32-087-9468

Synthetic Engine Oil
5W-30

APPLICATIONS

LUPROMAX ZELOS 5000 5W-30 is designed to optimize performance and protection for modern passenger cars where API SM (and below) are recommended.

- LUPROMAX ZELOS 5000 5W-30 meets or exceeds the requirements of the industry and car manufacturer's standards required for modern high output, low emission, super or turbo-charged, DOHC or GDI petrol engines that are commonly found in the latest American, European and Japanese engine manufacturers.
- LUPROMAX ZELOS 5000 5W-30 is suitable for extreme engine stress conditions, where conventional oil often may not perform.

Suitable for modern high output, low emission, super or turbo-charged, DOHC or GDI petrol engines

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

AVAILABLE PACKAGING

20 liters pail/ 200 liters drum

TYPICAL PROPERTIES

Properties			Method	LUPROMAX ZELOS 5000
ISO Viscosity Grade			SAE J 300	5W-30
Kinematic Viscosity	@40°C	cSt	ASTM D445	67.89
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.25
Viscosity Index			ASTM D2270	159
TBN	mgKOH/g		ASTM D2896	7.14
Flash Point	°C		ASTM D92	220
Pour Point	°C		ASTM D97	-36
Density	@15°C	kg/l	ASTM D4052	0.859

HEALTH, SAFETY & ENVIRONMENT

- Health and Safety

LUPROMAX ZELOS is unlikely to present any significant health or safety hazard when used properly in the recommended application provided in the Material Safety Data Sheet (MSDS) are followed. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained upon request through your sales contract office, or via the internet.

- Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.






Revolutionizing the Lubrication Industry through Heat Activated Technology

For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed by:



Headquarters & Far East Office:
Magna International Pte Ltd

10H Enterprise Road
Singapore 629834

Tel (65) 6788-1228

Fax (65) 6785-1497

Email info@magnachem.com.sg

Website

<http://www.magnachem.com.sg>

Indonesia Office:

PT Magna Indonesia

Central Park Office Tower,
18th floor Suite #2

Jl. Letjen S. Parman Kav. 28
Jakarta Barat 11470

Tel (62) 021-2903 4333

Fax (62) 021-2903 4260

Email contactus@lupromax.co.id

North America Office:

1450 Government Rd West
Kirkland Lake Ontario P2N 2E9
Canada

Email magna@vappro.com

Australia Office:

6/632-542 Hampton Street,
Hampton VIC 3188
Melbourne Australia

Email

nelsoncheng@magnaaustralia.com.au

Website

<http://www.magnaaustralia.com.au>

ISO 9001



Certificate No: AJA00/2706

ISO 14001



Certificate No: AJA13/16783

This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

LUPROMAX®