



Your Partner in Chemical Innovation

PRODUCT INFORMATION

ALUMINUM WHEEL CLEANER & BRIGHTENER

Function: Metal Cleaner	Application: Aluminum Surfaces	Form: Liquid
-----------------------------------	--	------------------------

DESCRIPTION

Aluminum Wheel Cleaner & Brightener provides rapid and effortless cleaning and removal of aluminum oxides, road film, diesel smoke residues and other dulling films from aluminum truck wheels, trailers and bodies. This aluminum cleaner is formulated using wetting agents, penetrants, heavy-duty emulsifiers and a blend of inorganic acids. The product penetrates quickly through oxides, road film and diesel smoke deposits to dissolve and emulsify them so that they can be rinsed away. Rinse agents provide a "sheeting" action for film-free rinsing. Cleaned surfaces dry streak-free.

FEATURES

- Economical to use because of variety of dilution ratios.
- Dilutable with water up to 1part product to 20-part water
- Rapid action, normal cleaning and brightening operations will require only 3 to 5 minutes.
- Aluminum Wheel Cleaner becomes more economical with each use. The more frequently the surface is cleaned and brightened, the lower the concentration required.
- Regular use will keep aluminum surfaces looking new

APPLICATIONS

Wheels, Tanks, Truck Bodies and any other surface that is coated with aluminum oxide.

DIRECTIONS FOR USE

1. Aluminum Wheel Cleaner can be sprayed on or applied with a long handle brush or sponge.
2. Cool the surface before cleaning by flushing off with water.
3. Begin the application on the bottom surface and work upward.
4. Apply with a circular motion, agitating enough to loosen the surface film.
5. Allow the Aluminum Wheel Cleaner to remain on the surface approximately 1 to 2 minutes, then hose off with clean water.

* It is recommended that only a small section be cleaned at a time before moving on to the next area to be cleaned

DILUTION SCALE: For Heavy Oxidation and corrosive removal, use 1 part of aluminum Wheel Cleaner to 5 parts water. To remove light corrosion or oxidation, use 1-part Aluminum Wheel Cleaner to up to 20 parts of water. The dilution used can be varied according to the condition of the surface being cleaned.

Note: Add product to water, not water to product.

PACKAGING

- 4L Jug
- 20L Pail
- 205L Drum



North & South America



Warehouse Address

1450 Government Road West
Kirkland Lake, Ontario P2N 2E9 Canada
Tel: 416 479 9151 Fax: 888 317 1993
Email: magna@vapro.com
www.vapro.com

Office Address

33 Blue Heron Drive
Orangeville, Ontario L9W 5K5 Canada
Tel: 416-479-9151
Fax: 888-317-1993