

VAPPRO®

VAPOUR CORROSION INHIBITOR

Your Corrosion Solution

PRODUCT INFORMATION

VAPPRO 819 ARM-GUARD

NATO STOCK NUMBER: 6850-32.076-8150

Function:

Vapour Corrosion Inhibitor (VCI)

Application:

Firearm Protector

Form:

Liquid

INTRODUCTION

VAPPRO is your key to operational superiority. **Magna** has successfully preserved military vehicles, weapons and weapon systems, optical and electronic equipment in Asia Pacific Region.

VAPPRO 819 Arm-Guard is specially developed to enhance operational readiness. **VAPPRO 819 Arm-Guard** bears the **NATO STOCK NUMBER: 6850-32.076-8150**.

DESCRIPTION

VAPPRO 819 Arm-Guard is a light brown thixotropic liquid with VCI corrosion inhibitors and oil based or solvent based carriers. The residual film, after solvent evaporation, is highly resistant to salt water and salt spray, making **VAPPRO 819 Arm-Guard** particularly useful in military, marine, industrial, and off-shore rust proofing applications. **VAPPRO 819 Arm-Guard** provides optimal corrosion protection for up to 10 years, for long term storage of small arms.



FEATURES

- Dry to touch film properties allow protected metal surfaces to be easily handled
- Little surface preparation, as **VAPPRO 819 Arm-Guard** to the pre-rusted surfaces
- A thixotropic liquid, and self-healing. Thus, resistant to sag, run-off, and flow.
- Universal protection for ferrous and non-ferrous metals and alloys
- The non-conductive film with high resistivity and insulating properties effectively prevents galvanic corrosion between dissimilar metals
- Has moisture displacing characteristics
- Thermally stable coatings over a broad temperature range (30°C - 95°C)
- Provides high levels of corrosion resistance, up to 10 years' indoor protection in corrosive atmospheres
- Moisture displacing and penetrating film characteristics
- Easy removal by petroleum solvents or **VAPPRO AWM** sonic wash machines



APPLICATIONS

Preservation of Weapons

- *Long term storage of small arms – M16, AR15, SAW Ultimax, GPMG, 84/ 106 Recoilless Gun, 81mm / 120mm mortar etc.*

DIRECTIONS FOR USE

- Dipping, spraying or brushing are recommended methods of application. Film thickness of 2 mils to 5 mils
- For maximum protection use **VAPPRO 819 Arm-Guard** in concentration form
- For short term protection **VAPPRO 819 Arm-Guard** can be diluted 1:1 with mineral spirits
- **VAPPRO 819 Arm-Guard** can be applied over pre-rusted or oily surfaces
- Application does not require heating of inhibitor solution or increased temperatures for drying

PACKAGING

- 20 Litre pail & 200 Litre drum

PHYSICAL PROPERTIES

Appearance	Dark brown thixotropic liquid
Specific Gravity	0.92 at 25°C
Film type	Dry waxy film
Carrier	Mineral spirits/Naphthenic oil
Flash point	Concentrate form 232°C
Viscosity	cps at 23°C 8000 cps

North & South America



Warehouse Address

1450 Government Road West
Kirkland Lake, Ontario P2N 2E9 Canada
Tel: 416 479 9151 Fax: 888 317 1993
Email: magna@vapro.com
www.vapro.com

Office Address

33 Blue Heron Drive
Orangeville, Ontario L9W 5K5 Canada
Tel: 416-479-9151
Fax: 888-317-1993