



PRODUCT INFORMATION

VAPPRO 886

VCI ACRYLIC COATING

Function: Vapour Corrosion Inhibitor (VCI)	Application: Acrylic Coating	Form: Liquid
--	--	------------------------

DESCRIPTION

VAPPRO 886 is a water based corrosion inhibitor developed as a complete replacement for oil based rust preventives. Its aqueous solutions are heat stable. **VAPPRO 886** is designed for corrosion protection of bare metal substrates in sheltered environment and in many instances, it can be coated over with paints and primers without removal.

VAPPRO 886 is a non-toxic water based corrosion inhibitor. Specially developed to replace conventional, toxic and health hazard oil based rust preventives.

VAPPRO 886 is made from Acrylic Copolymer emulsion with a mixture of non-toxic organic inhibitors. Its formulation offers unprecedented advancement in outdoor corrosion protection and will successfully provide up to 24 months of protection in harsh, outdoor unsheltered conditions.

VAPPRO 886 is non-flammable, weldable, biodegradable and has excellent salt spray resistance. It provides a fast drying, clear coating and a non-flammable protective barrier that allows visual inspection of the metal surface after application.

FEATURES

- Water based, safe, non-toxic and biodegradable
- Non-flammable and weldable
- Forms a fast drying, glossy coating
- Forms a clear and dry film which renders attractive appearance to protected parts
- Heat stable
- Minimal surface preparation required; can be applied on damp surfaces
- Excellent salt spray resistance
- Can be over-coated with most generic topcoats, epoxies, polyurethanes and alkyds
- Excellent inter-film adhesion
- For use on ferrous and non-ferrous metals
- Eliminates cleaning and housekeeping problems associated with oils
- Unique vapour phase action also protects uncoated and difficult-to-reach areas
- Conforms to FDA CFR-21 Parts: 175, 105, 175.300, 176.170, 176.180

APPLICATIONS

- Castings, forgings, tubular parts, machined and honed metal components
- Precision machined parts, structural steel, sintered metals, bars and roll stock

VAPPRO 886 can also be used for smaller applications such as:

- Water pumps, electric motor housings, exposed shafting, pipe, tubing, engines, metal enclosures, conduit, housing etc.

PACKAGING

- 20 Litre pail
- 200 Litre drum

PHYSICAL PROPERTIES

Appearance	White, translucent, liquid
Odour	Almost odourless
pH @25°C	8.1
Boiling Point	ca. 100 °C as water
Melting Point	- °C
Softening Point	Not applicable °C seta flash cc
Flash Point	N.A.
Flammability	N.A.
Explosive limit	N.A.
Oxidizing properties	N.A.
Vapour Pressure at 20°C	23 mbar as water
Relative density at 20°C	1.04 g/cm ³
Solubility	Miscible in water
Viscosity at 25°C	75 mPa's Brookfield



North & South America



Warehouse Address

1450 Government Road West
Kirkland Lake, Ontario P2N 2E9 Canada
Tel: 416 479 9151 Fax: 888 317 1993
Email: magna@vapro.com
www.vapro.com

Office Address

33 Blue Heron Drive
Orangeville, Ontario L9W 5K5 Canada
Tel: 416-479-9151
Fax: 888-317-1993