SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

Product Identifier: Magna 240

Other means of identification:Magna Glass Window CleanerRecommended use:Window cleaning solventManufacturer's Name:Magna Chemical Canada Inc.

Address: 1450 Government Road West, Kirkland Lake, ON P2N 2E9

Phone: 705 642 3352 or 416 479 9151 **Emergency Only:** Canutec 24hr Tel: 613-996-6666

SECTION II – HAZARDS IDENTIFICATION

GHS CLASSFICATION:

Flammable liquid: Category 2

GHS LABEL ELEMENTS SYMBOL(S)



SIGNAL WORDS:

Danger

GHS HAZARDS STATEMENTS:

H225: Highly flammable liquid and vapour.

H320: Causes eve irritation

GHS PRECAUTIONARY STATEMENTS:

PREVENTION

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242: Use only non-sparkling tools.

P243: Take precautionary measures against static discharge.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/ face protection.

RESPONSE:

P303 + P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338: IF IN EYE: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313: If eye irritation persists: Get medical advice/attention.

P370+P378: In case of fire: Use *CO*₂ or powder for extinction.

STORAGE

P403+P235: Store in a well-ventilated place. Keep cool.

SECTION III – COMPOSITION / INFORMATION ON INGREDIENTS		
Ingredient Name:	Weight %:	CAS#
Isopropyl Alcohol	30-40	67-63-0
Non-ionic surfactant	1-3	127087-87-0
Water	50-70	7732-18-5

SECTION IV – FIRST AID MEASURES

Inhalation

Remove person to an uncontaminated area. Administer oxygen if necessary. If breathing has stopped, administer CPR.

Skin Contact

Remove contaminated clothing. Wash affected area with water. If irritation persists, call physician.

Eye Contact

Immediately flush with plenty of water for at least 15 minutes. Make sure to flush under eyelids. Consult physician immediately.

Ingestion

DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION V – FIRE FIGHTING MEASURES

Suitable Fire-extinguishing media

Foam (alcohol-resistant foam), powder, and carbon dioxide are effective fire-extinguishing agents.

Specific hazards arising from the chemical

CO₂, Dry Chemical; or Foam.

Special protective actions for fire fighters

Firemen should wear self-contained breathing apparatus and protective clothing when fighting chemical fires.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance of selection of personal protective equipments see Chapter 8 of this Safety Data Sheet.

Environmental Precautions

Prevent spills from entering drains or sewers and contact with soil.

Methods and materials for contaminated and cleaning up

For small spills, carefully flush with water. For large spills, contain spills. Do not touch or walk through spilled material. Dike ahead of large spills to prevent run-off. Mop, pump or absorb onto suitable absorbent and place in container for reuse, recycle or proper disposal. Flush area with water to eliminate residues.

SECTION VII - HANDLING AND STORAGE

Precautions for safe handling

Do not swallow. Avoid eyes and skin contact. Wear recommended protective equipment. Use only with adequate ventilation. Wash thoroughly after handling material.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed when not in use. Store in dry, cool, well-ventilated area away from incompatibles.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

SG OEL: (TWA) 400 ppm SG OEL: (STEL) 500 ppm ACGIH: (TWA) 200 ppm ACGIH: (STEL) 400 ppm

Appropriate engineering control measure

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include: Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Eye washes and showers for emergency use.

Individual protection measure

Protective Gloves

Neoprene/ PVC gloves.

Eye Protection

Safety glasses with side shields are recommended.

Respiratory Protection

Not required under normal use conditions with good general ventilation.

Hygienic Work Practices

Wash hand after use. Do not eat, drink or smoke in immediate area.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES		
Appearance Physical State	Liquid	
Color	Blue	
Odour	Characteristic	
Odour Threshold	Odour Threshold Not applicable	
pH	Not applicable	
Melting Point	Not applicable	
Freezing Point	-88°C (100% IPA)	
Boiling Point	82°C - 83°C (100% IPA)	
Flash Point	21°C	
Evaporation Rate	1.5 (ASTM D3539, nBuAc =1) (100% IPA)	
Flammability (solid, gas)	Not applicable	
Upper explosive limit	12% (100% IPA)	
Lower explosive limit	2% (100% IPA)	
Vapour Pressure	4100 Pa @ 20°C (100% IPA)	
Vapour Density	2 @ 20°C (100% IPA)	
Relative Density $0.95 \text{ g/cm}^3 \pm 0.025 \text{ @ } 20^{\circ}\text{C}$		
Solubility	Completely miscible	
Partition coefficient: n-octanol/water	Not applicable	
Viscosity	Free Flowing Liquid	
Auto-ignition Temperature	425°C (100% IPA)	

SECTION X – STABILITY & REACTIVITY

Reactivity/Incompatible materials

React with strong acid and oxidizing materials.

Chemical stability

Stable under normal temperature and pressure.

Possible of hazardous reaction

Data not available.

Conditions to avoid

Heat, contact with incompatible materials, open flame.

Hazardous decomposition products

Burning may produce oxide of carbons and other substances.

SECTION XI – TOXICOLOGICAL INFORMATION

Acute Oral Toxicity LD50 > 2000 mg/kg (Rat)

Acute Dermal Toxicity LD50> 2000 mg/kg (Rat)

Acute Inhalation Toxicity LC50> 20 mg/L/8 Hours (Rat)

PRIMARY ROUTES OF EXPOSURE

Xeye Xskin Xoral Inhalation Other

Eyes: Classified as an eye irritant. Contact with the eyes may give rise to irritation and stinging. No permanent damage if treated immediately.

Skin: Prolonged and persistent contact may lead to dermatitis through skin de-fatting.

Inhalation: Excessive exposure to mists caused by atomising systems may cause irritation to eyes and respiratory tract.

Carcinogenicity: The ingredients of this product are not classified as being carcinogenic by ACGIH (American Conference of Governmental Industrial Hygienists) or IARC (International Agency for Research on Cancer), not regulated as carcinogens by OSHA (Occupational Safety and Health Administration), and not listed as carcinogens by NTP (National Toxicology Program).

REPRODUCTIVE TOXICITY INFORMATION:

Mutagenicity: No Embryotoxicity: No. Teratogenicity: No.

Reproductive Toxicity: No.

SECTION XII - ECOLOGICAL INFORMATION

Eco-toxicity: Acute Toxicity:

Fish: Low toxicity: LC/EC/IC50 > 100 mg/l

Aquatic Invertebrates: Low toxicity: LC/EC/IC50 > 1000 mg/l **Algae:** Expected to have low toxicity: LC/EC/IC50 > 1000 mg/l **Microorganisms:** Low toxicity: LC/EC/IC50 > 1000 mg/l

Mobility: Dissolves in water. If product enters soil, it will be highly mobile and may contaminate groundwater. **Persistence/degradability:** Readily biodegradable meeting the 10-day window criterion. Oxidises rapidly by

photo-chemical reactions in air.

Bioaccumulation: Not expected to bioaccumulate significantly.

SECTION XIII – DISPOSAL CONSIDERATIONS

Dispose of in accordance with existing Federal, State and local environmental regulation.

SECTION XIV – TRANSPORT INFORMATION

Land (as per ADR classification): Regulated

Class: 3

Packing Group: III

Hazard Identification No. 33

UN No.: 1987

Danger Label (Primary Risk): 3

Proper Shipping Name: ALCOHOLS, N.O.S (contains isopropanol)

IMDG

Identification Number: UN 1987

Proper Shipping Name: ALCOHOLS, N.O.S (contains isopropanol)

Class / Division: 3 Packing Group: III Marine Pollutant: NO

IATA (Country variations may apply)

UN No.: 1987

Proper Shipping Name: ALCOHOLS, N.O.S (contains isopropanol)

Class / Division: 3 Packing Group: III

SECTION XV – REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Canadian WHMIS Classification: Class B, Division 2

EC Label Name: ISOPROPYL ALCOHOL

EC label/EC Number: 200-661-7

EC Classification: Highly flammable. Irritant.

EC Annex I Number: 603-117-00-0 EC Symbols: F Highly flammable.

Xi Irritant.

EC Risk Phrases: R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

EC Safety Phrases: S7 Keep container tightly closed.

S16 Keep away from sources of ignition - No smoking.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

AICS : Listed.
DSL : Listed.
INV (CN) : Listed.

ENCS (JP) : Listed. (2)-207 ISHL (JP) : Listed. 2-(8)-319

TSCA : Listed.

EINECS : Listed. 200-661-7

KECI (KR) : Listed, KE-29363

PICCS (PH) : Listed.

SECTION XVI – OTHER INFORMATION

H.M.I.S rating: Health - 1, Fire -3, Reactivity -1, Protection -B

Where

0 = Insignificant

1 = Slight A = Safety Glass

2 = Moderate B = Safety Glass & Gloves

3 =Serious C =Safety Glass, Gloves & Apron 4 =Severe D =Face Shield, Gloves & Apron

R-phrase(s):

R11 Highly flammable. R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

Uses and Restrictions: Use as a solvent only in industrial manufacturing processes.

MSDS Distribution: The information in this document should be made available to all who may handle the product

Date: 15 January 2019

Replaces edition of: 10 March 2016

H.M.I.S: Hazardous Materials Identification System

CAS#: Chemical Abstracts Service Number

ACGIH: American Conference of Governmental Industrial Hygienists

OSHA: Occupational Safety and Health Administration

TLV: Threshold Limit Value **PEL**: Permissible Exposure Limit **REL**: recommended exposure limit

TWA8: The time weighted average concentration for a normal 8-hour workday and a 40-hour workweek, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.

N.A: Not applicable N/E: Not establish N.D: Not determine

C: Ceiling (The concentration that should not be exceeded during any part of the working exposure).

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to be best knowledge of Magna Chemical Canada Inc. The data on this sheet relates only to the specific material designated herein. Magna Chemical Canada Inc. assumes no legal responsibility for use or reliance upon these data. Magna Chemical Canada Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.