

Your Corrosion Solution

PRODUCT INFORMATION

VAPPRO 855 ANTI-CORROSION OIL

Function:

Vapour Corrosion Inhibitor (VCI)

Application: Coating

Form: Liquid

DESCRIPTION



VAPPRO 855 is a light brown anti-corrosion oil blended with a solvent.

VAPPRO 855 is a mobile liquid that possesses excellent water displacement properties. When the solvent evaporates it deposits a soft film on the metal surface providing a high degree of protection.

VAPPRO 855 provides excellent corrosion protection on multimetals leaving a transparent film on the metal making visual inspection easy.

FEATURES

- Multi-metal protection
- Applicable to Federal Specification VV-P-216
- Transparent film for easy visual inspection
- De-watering properties
- Multi-purpose de-watering fluid provides a film with good protective qualities

APPLICATIONS

Classified as a medium-term protective, **VAPPRO 855** is useful for a variety of purposes in machine shops and in heavy machinery and industrial manufacturing plants.

It is ideal for treating machine tools and offers excellent protection during storage periods.

VAPPRO 855 is recommended for the protection of sheet metal panels. The residual greasy film can serve as a mild press-working lubricant.

PHYSICAL PROPERTIES	
Appearance	Liquid
Color	Light brown
Flash Point	40oC
Specific Gravity	0.83 + - 0.5
Film Thickness (approximate)	3 microns
Drying Time	40 ins (90% solvent loss)
Area Coverage (approximate)	72 sq. m/l

DIRECTIONS FOR USE

Immersion is best but VAPPRO 855 may also be applied by brushing or spraying

DURATION OF PROTECTION

- Indoors 14 months
- Outdoors 3 months*

DIRECTIONS FOR REMOVAL

Magna 106 Alkaline Degreaser is suitable for the removal of VAPPRO 855.

PACKAGING

- 20L Pail
- 200L Drum



Manufacturing Facility 1450 Government Rd., West Kirkland Lake, ON P2N 2E9 Canada Contact Information T: 1 (416) 479-9151 F: 1 (888) 317-1993 E: magna@vappro.com Websites www.vappro.com www.vappro.ca

^{*}Period specified for outdoor use assumes primary protection from the elements by tarpaulin or another form of covering